



PRESS INSERT 260 SERIES — FLANGED BRASS

Part Number	Thread Size	L	A	B	T	Hole Size*	Minimum Depth
		(in.)	(in.)	(in.)	(in.)	(in.)	(in.)
260-002-BR	2-56	.156	.187	.135	.017	.125	.173
260-004-BR	4-40	.188	.218	.166	.020	.156	.215
260-006-BR	6-32	.250	.249	.199	.026	.188	.259
260-008-BR	8-32	.313	.280	.230	.032	.219	.302
260-332-BR	10-32	.375	.312	.262	.039	.250	.345
260-4-BR	1/4-20	.500	.375	.326	.049	.313	.432
260-5-BR	5/16-18	.563	.437	.389	.060	.375	.518
260-6-BR	3/8-16	.625	.500	.451	.061	.438	.604
260-M3-BR	M3-0.5	.188	.218	.166	.020	.156	.215
260-M4-BR	M4-0.7	.313	.280	.230	.032	.219	.302
260-M5-BR	M5-0.8	.375	.312	.262	.039	.250	.345
260-M6-BR	M6-1.0	.500	.375	.326	.049	.313	.432
260-M8-BR	M8-1.25	.563	.437	.389	.060	.375	.518

* Hole size requirements may vary depending on a number of factors, including material and tools. We recommend that you test your particular application before ordering. We gladly supply free samples.