



PRESS INSERT 240 SERIES — FLUSH STAINLESS STEEL

Part Number	Thread Size	L	A	B	Hole Size*	Minimum Depth
		(in.)	(in.)	(in.)	(in.)	(in.)
240-002-CR	2-56	.156	.125	.135	.125	.173
240-004-CR	4-40	.188	.156	.166	.156	.215
240-006-CR	6-32	.250	.187	.199	.188	.259
240-008-CR	8-32	.313	.218	.230	.219	.302
240-3-CR	10-24	.375	.250	.262	.250	.345
240-332-CR	10-32	.375	.250	.262	.250	.345
240-4-CR	1/4-20	.500	.312	.326	.313	.432
240-5-CR	5/16-18	.563	.375	.389	.375	.518
240-6-CR	3/8-16	.625	.437	.451	.438	.604
240-M3-CR	M3-0.5	.188	.156	.166	.156	.215
240-M4-CR	M4-0.7	.313	.218	.230	.219	.302
240-M5-CR	M5-0.8	.375	.250	.262	.250	.345
240-M6-CR	M6-1.0	.500	.312	.326	.313	.432



* Hole size requirements may vary depending on a number of factors, including material and tools. We recommend that you test your particular application before ordering. We gladly supply free samples.